



# CAT6 ECCS OUTDOOR ARMORED INSTALLATION CABLE

Zyxel category 6 ECCS Outdoor Armoured Cable consist of 8 Copper Conductors, 2 conductors twisted together to form a pair. 4 Pairs are laid up together and separated by special type of Cross Separator. Armouring is done over inner sheath with Electrolytic Corrugated Coated Steel Tape.

## Application

### Wireless Wi-Fi Networks

Data interface rates have increased from 1G Base-T to even 10G Base due to significant rise in the need for WiFi connectivity.

### Local Area Network

Last mile connectivity is is still feasible solution for business even in FTTB environment.

### Surveillance & PoE Application

Requirement for cabling systems have become more stringent due to emergence of Power over Ethernet (PoE) technology.

## Specifications

Physical Characteristics	
Application	Cat6 Outdoor Application wherever the high-speed data transfer is required to full fill the device requirement.
Standards	ISO/IEC 11801 2nd ed.; IEC 61156-5 2nd ed.
Fire Rating	IEC 60332-1; IEC 60754-2; IEC 61034;
Conductor	Solid Bare Electrolytic Copper Ø 0.505 mm ± 0.02 mm
Insulation	Ø 0.990 mm ± 0.05 mm
Twisting	Total 4 Pairs. 2 cores per pair.
Foil Shielding	None
Braiding	None
Inner Sheath	PVC Grey
Outer Sheath	PE with UV Properties
Armour	ECCS Steel Tape
Pair Colors	Blue – Blue/White Orange – Orange/White Brown – Brown/White Green – Green/White
Protection	Armored for protection from harsh weather and rodents


Generic Data	
Description & Length	Armored Cable Cat 6 / 305 Mtr
Cable Type	ECCS – Armored
Conductor Diameter mm	0.505 ± 0.02 mm.
Core Diameter mm	0.990± 0.05 mm.
Shielding	None
Nominal Outer Diameter (mm)	10.0 ± 0.7 mm.
Conductor Gauge	24 AWG
Pair Separator	PE Cross – Member (+) Separator

Electrical Specifications (20 ± 3 °C)	
Telecommunication Standards	ANSI/TIA-568-C.2 Category 6 and ISO 11801 Class E
Operating Frequency – Min.- Max.	250 Mhz
Nominal Velocity of Propagation (NVP)	69%
Operating Voltage – Max.	90V
PoE Compliance	IEEE802.3af and IEEE 802.3at
Maximum Temperature Rating	Storage -20°C to +60°C. At the installation time: -20°C to 75°C. Operational Temperature: -20°C to 60°C
Max. Resistance Unbalance	≤ 5%
Max. Conductor Resistance	95.8 Ω/km
Max. Mutual Capacitance	5.6 nF/100 m max.
Capacitance Unbalance (pair to ground)	330 pF/100 m max
Nominal Characteristic Impedance	(100 ± 15) Ω / 100 MHz
Delay Skew	≤ 45 ns/100m
Bending Radius	≤ 20 X Cable Dia
Packaging	305 Mtr Packed in Wooden Drum

# High Frequency Electrical Parameters

Frequency Mhz	ATT (dB/100m) max.	NEXT (dB) min	PS.NEXT (dB) min.	ACRF (dB@100 m) min.	PS.ACRF (dB@ 100 m) min	Return Loss (dB/100m)
1	2.3	65	62	63.3	60.3	19
4	4.2	63	60.5	51.2	48.2	19
8	5.8	58.2	55.6	45.2	42.2	19
10	6.5	56.6	54	43.3	40.3	19
16	8.2	53.2	50.6	39.2	36.2	18
20	9.2	51.6	49	37.2	34.2	17.5
25	10.2	50	47.3	35.3	32.3	17
100	20.9	39.9	37.1	23.3	20.3	12
200	30.1	34.8	31.9	17.2	14.2	9
250	33.9	33.1	30.2	15.3	12.3	8
300	37.4	31.7	28.8	13.7	10.7	7.2
400	43.7	28.7	25.8	11.2	8.2	6
500	49.3	26.1	23.2	9.3	6.3	6

## Construction Of Cable



### Product

Model  
**ZY60CCG4F0135-ES**

Disclaimer: Zyxel Networks, Zyxel logo is a registered trademark of Zyxel Group, and may be registered in other countries; all other trademarks listed herein belong to their respective owners. This information printed here is correct at the time of publication and as per testing of the components under standard, specified and controlled environment. Specifications are subject to change without any further notice.

For other Zyxel Solutions , visit us on the web at [www.zyxel.com](http://www.zyxel.com)

